

OPTIONAL EQUIPMENT

HOSE ASSEMBLIES



10756 - 18" overall length hose with giant button head coupler (10670) and swivel (10748). 1/4" NPT(m) inlet x giant button head coupler outlet.



10750 - 18" overall length hose with giant button head coupler (10630). 1/4" NPT(m) inlet x giant button head coupler outlet.



10775 - Screw Connection Hose Assembly for lubricating vent cap fittings. 18" overall length hose with screw connection coupler. 1/4" NPT(m) inlet x 1"-14 UNS(f) outlet.



10660- 18" overall length hose with giant button head coupler (10850), gage tee (10844), gage and cover (11475), "Z" swivel (10744), swivel (10641), shut off relief valve (10990). 1/4" NPT (m) inlet x giant button head coupler outlet.



10876- 18" overall length hose with giant button head coupler (10850), gage tee (10844), gage and cover (11475), swivel (10641). 1/4" NPT (m) inlet x giant outlet.



10650- 18" overall length swivel hose with giant button head coupler (10630), gage tee (10844), gage and cover (11475). 1/4" NPT (m) inlet x giant button head coupler outlet.

OTHER HOSE LENGTHS, END COMBINATIONS AND ASSEMBLIES ARE AVAILABLE.

HOSE ASSEMBLY RATING: Working Pressure 10,000 psi, Burst Pressure 23,000 psi. **WARNING:** Hoses are for use with hand operated grease guns only. Inquire regarding additional warnings. Consult "Rubber Manufacturers Association Hose Handbook" for proper operating procedure.

GAGES

Stainless construction
1/4" NPF (m) b.ver moerr

10873 - 15,000 psi
21/2" face

10599 - 20,000 psi

11184 - Gage cover for 2-1/2" O

11475 - 10873 & 11184



GAGE TEES (machined)



10637 - 1-1/4" hex

10844 - 1" hex

10620 - 1-1/4" hex, includes check valve

Rated to 10,000 psi

By using a Dualco Gage Tee an adapter is not required. 1/4" NPT(m) x 1/4" NPT(f).

SHUT OFF/RELIEF VALVE



10990 - 1/4" NPT(m) x 1/4" NPT(f).

OTHER GAGES ARE AVAILABLE

SPECIAL ORDER TEES ARE AVAILABLE

OTHER SIZES ARE AVAILABLE

SWIVELS

ADVANTAGES

Easy handling of operational grease gun is assured.

Hose damage is reduced. Pressurized hoses will not twist.

10744 - 1/4" NPT(m) x 1/2"-27 NS taper (m)

10642 - 1/4" NPT(m) x 1/2"-27 NS taper (m)

10641 - 1/4" NPT(m) x 1/2"-27 NS taper (m)

10748 - 1/8" NPT(m) x 7/16"-27 NS (m)

OTHER SIZES ARE AVAILABLE



10744 - "Z"

10642 - 90°

10641 - Straight

10748 - Straight

CARRY STRAP ASSEMBLY



FEATURES

Weight - 3-3/4 oz.

Lightweight and strong. Includes shoulder pad, hooks, rings and link.

Adjustable and extends to 46"

10616 - For Screw Prime Gun Assemblies

10644 - For Hydraulic Grease Gun Assemblies

DUALCO WILL CUSTOM DESIGN AND MANUFACTURE PRODUCTS TO SUIT SPECIFIC REQUIREMENTS.



8404 BRANIFF, HOUSTON, TEXAS 77061 * 713-644-1164 * FAX 713-644-7761

TOLL FREE 877-538-2526 OR 877-5DUALCO

E-MAIL: dualco@dualco-inc.com * www.dualco-inc.com