



DUALCO • 8404 Braniff, Houston, Texas 77061  
 713-644-1164 • FAX 713-644-7761  
 www.dualco-inc.com  
 E-Mail: dualco@dualco-inc.com

All Rights Reserved. © Copyright 2020 DUALCO Inc.



Environmentally  
 Friendly & Non-Toxic.  
 Engineered & Made in the U.S.A.

## Product Specification Sheet

# Premium Lubricant / Sealant

**DUALCO Premium (P)** is a combination lubricant and sealant. This material is suitable for use in plug, ball, and gate valves. Premium meets U. S. Government Specification **SAE-AMS-G-6032 "Grease, Plug Valve, Gasoline and Oil Resistant, NATO Code Number G-363, Metric."** Premium is 100% synthetic. It is made of stable, non-reactive materials and is designed for use in valves controlling the flow of natural gas, crude oil, gasoline, jet fuel, lubricating oils or mixture of these products. It is water resistant, has excellent "plating out" characteristics, is inhibited for H<sub>2</sub>S (<1000 ppm) and CO<sub>2</sub> (< 40%) applications and is resistant to organic acids and caustic solutions. Premium is a special service material. Laboratory tests have shown this material reduces operating torque up to 50%. Premium should be used where extreme pressures prevail. This material is designed for use in close tolerance valves.

Although it contains an excellent antioxidant, **DO NOT** use this material in oxygen service. For Industrial use only.

### Packaging

- DUALCO Premium is available in sticks, cartridges and all sizes of bulk containers.

### Physical Properties

- NLGI Consistency Number 3-3.5
- Cone Penetration (ASTM D-217) 160-175
- Color: Yellow to Brown
- Odor: Mild to Neutral
- Service Life: Extended
- Texture: Tacky
- Consistency: N/A
- Dropping Point: ° F (ASTM D-566) None
- Oil Separation: % wt. Loss (ASTM D-1742) min.
- Corrosion Inhibitor: Imidazoline Derivative Additive
- Rust Preventive Test (ASTM D-1743) Passed
- Diester Type (Extreme Pressure Resistant) Additive
- Oxidation Stability, (ASTM D-942) 10 max.
- Temperature Range: -50° to 450° F
- Base Oils: Proprietary Synthetics

### Features

- 100% Synthetic Oils
- Water Insoluble and Washout Resistant
- High Metal Adhesion
- Excellent Corrosion Resistance
- Resistant to H<sub>2</sub>S (< 1000 ppm) and CO<sub>2</sub> (< 40%)
- Suitable for use in all hydrocarbon services
- Contains no perfumes, dyes, or heavy metals
- Non-Toxic, Non-Hazardous – Environmentally Friendly.

### Application Method

- Grease Gun or Automated Equipment (Air, Air/Hydraulic, Hydraulic or Manual)



Made in the USA

The information and the recommendations made in this data sheet are based upon collected data and believed by us to be correct. However, no guarantee or warranty of any kind, expressed or implied is made herein with respect to the merchandise described; and we assume no responsibility for the results or the use thereof.

ESTD 1960

