

Got Valves?

Model

12610

ESTD




1960

SOLM[®] ACT-12

Patents Pending

Automated Frac Tree/Manifold Lubrication & Valve Actuation Systems

- Fully Automated
- Lubricates Multiple Valves
- Valve Actuation
- High Pressure



SOLM[®] ACT-12 is Part of the
Dualco Automated Multi-Valve-Point
(D.A.M.[®]) Lubrication System Family

• Keeps Personnel Out of the Red Zone!

Automatically lubricates up to 12 valves, while maintaining accurate lubrication levels without under or over lubricating.

Automated lubrication:

- Uses an estimated 33% less grease than manual lubrication.*
- Applies Grease evenly to valve seats and achieves better grease coverage.
- Applies metered amounts giving your valves the best protection and performance.
- Nullifies the tradition of over lubricating. (Pumping grease in until it oozes out.)
- Globally can save millions on grease and up to 300,000 tons of CO₂ per annum.*

*For Reference Only

Reduces:

- Labor
- Waste
- Downtime
- Environmental Impact

Increases:

- Valve Life
- Safety
- Productivity
- Profits

Applications:

- Fracturing
- Wellheads
- Offshore
- Manifolds

Specifications

Operating Voltage	24 volts (DC) or 110 volts (AC)	
Ambient Temperature	-4°F to 104°F (-20°C to 40°C)	
Discharge Hoses	Various Lengths Available / Application Dependant	
Lubricant	Bulk / NLGI 1-6	
Lube Source	5 gal pail, 16 gal drum, 55 gal drum	
Pump	Type	2 gal Air Hydraulic, 5, 16 or 55 gal Air or Custom
	Air Supply Rate & Pressure	≥ 40 CFM, 100 - 125 psi
Lubricant Pressure Range	500 - 10,000 psi (34 - 689 bar)	
Number of Valves	Standard	12 valves
	Custom	Expandable to 18 or more valves
Dimensions / Weight	6' x 4' x 5' (W.D.H.) / 1,100 lbs.	
Mobility	Fork Lift Slots	



Made in the USA

© 2024 Dualco Inc.

8404 Braniff
Houston, Texas 77061
Phone: 713-644-1164
dualco-inc.com

DUALCO[®]