

D.A.M.® Patent Pending

■ “Simultaneously Reducing Downtime and Labor while Increasing Safety.”

■ 54% of Valve Failures are Lubrication Shortfalls*

Model 13000-HP2

The 13000-HP2 Lubricates 2 to 8 High Pressure Valves.

The 13000-HP2 Uses Proprietary Dual 5lb Capacity Hydraulic Lubricant Cylinders

Up to 10,000psi



© 2024 DUALCO Inc.

Keeps Personnel Out of the Red Zone!

Automatically lubricates multiple valves, while maintaining accurate lubrication levels without under or over lubricating.

Reduces:

- Labor
- Waste
- Locking Valves
- Downtime
- Environmental - Impact

Increases:

- Valve Life
- Safety
- Productivity
- Profits


Applications:

- Fracturing
- Wellheads
- Pipelines
- Offshore
- Manifolds
- Industrial

54%

of Valve Failures are Lubrication related*

Reduces lubricant use up to 33%*





Dualco Automated Multi Valve-Point High Pressure Lubrication Systems

DAM HP-2 in the field automatically servicing large bore valves.



© 2024 DUALCO Inc.

Automated lubrication:


- Uses an estimated 33% less grease than manual lubrication.*
- Applies Grease evenly to valve seats and achieves better grease coverage.
- Applies metered amounts giving your valves the best protection and performance.
- Nullifies the tradition of over lubricating. (Pumping grease in until it oozes out.)
- Globally can save millions on grease and up to 300,000 tons of CO₂ per annum.*

*All Values are Approximate

Model **13000-HP2**

Specifications

Operating Voltage	24 volts (DC) or 110 volts (AC)	
Ambient Temperature	-4°F to 104°F (-20°C to 40°C)	
Discharge Hoses (2)	20 ft O.A.L.	
Lubricant	Stick or Bulk / NLGI 1 - 6	
Pressure Range	500 - 10,000 psi (34 - 689 bar)	
Enclosure	Dimensions Case (Excluding lifting eyes)	38" x 25" x 38" (W,D,H)
	Dimensions Cage-Skid (Excluding lifting eyes)	71" x 47" x 45" (W,D,H)
	Weight (fully outfitted, includes 2 discharge hoses)	1310 lbs.
	Material (Aluminum and Stainless enclosures available)	1/8" Steel Plate
	Mobility	Lifting eyes, Forklift slots & locking front panel.
Lube Source	5 lb capacity hydraulic cylinders	2
Pump	2 gal Air Hydraulic	2
	Air Supply Rate & Pressure	≥ 40 CFM 100 -125 psi

 Always Operate with Caution and Safety.

8404 Braniff
Houston, Texas 77061
Phone: 713-644-1164
Fax: 713-644-7761
www.dualco-inc.com

 713-644-1164

