

Product Specification Sheet

Peanut Butter Lubricant / Sealant

DUALCO Peanut Butter (PB) is a combination lubricant and sealant.

This inexpensive, nonabrasive, material is recommended for body fill of WKM style gate valves. Recommended for sealing valves in water, gas, condensate, oil and petroleum services, and for products such as gasoline, butane, hydrocarbon vapors, ammonia, glycerin, solvents and sour gas. **PB** is "creamy and spongy". By using this material, there is less friction and wear on pumps, packing assemblies, and friction parts than other conventional materials.

DO NOT use this material in oxygen service. For Industrial use only.

Packaging

• DUALCO Peanut Butter is available in sticks, cartridges and all sizes of bulk containers.

Physical Properties


- NLGI Consistency Number 2-3 (in bulk form)
- Color: Tan
- Odor: Mild to Neutral
- Service Life: Extended
- Texture: Tackv
- · Consistency: N/A
- Mica/Silica: less than .01
- Oil Separation: None
- Corrosion Inhibitor: Imidazoline Derivative Additive
- Density (weight) 9.3 to 9.55 lbs./gal.
- Diester Type (Extreme Pressure Resistant) Additive
- Temperature Range: -30° to 250° F
- Base Oils: Proprietary Synthetics

Features

- 100% Synthetic Oils
- Water Insoluble and Washout Resistant
- High Metal Adhesion
- Corrosion Inhibited
- Suitable for use in all hydrocarbon services
- Contains no perfumes, dyes, or heavy metals
- Non-Toxic, Non-Hazardous Environmentally Friendly.

Application Method

• Grease Gun or Automated Equipment (Air, Air/Hydraulic, Hydraulic or Manual)







The information and the recommendations made in this data sheet are based upon collected data and believed by us to be correct. However, no guarantee or warranty of any kind, expressed or implied is made herein with respect to the merchandise described; and we assume no responsibility for the results or the use thereof.

