



All Rights Reserved. © Copyright 2024 DUALCO Inc.

DUALCO • 8404 Braniff, Houston, Texas 77061  
713-644-1164 • FAX 713-644-7761  
www.dualco-inc.com  
E-Mail: dualco@dualco-inc.com



Environmentally  
Friendly & Non-Toxic.  
Engineered & Made in the U.S.A.

## Product Specification Sheet

# Valve Stem Packing Packing/Sealant

**DUALCO Valve Stem Packing (SP)** is a pumpable Packing and Sealant containing high temperature, proprietary, non-reactive fillers in a blend of synthetic oils. This material is recommended for use in hydrocarbon, steam and hot oil services. Valve Stem Packing contains fine to medium size TFE particles.

**DO NOT** use this material in oxygen service.

### Packaging

- DUALCO Valve Stem Packing is available in stick form and all sizes of bulk containers.

### Physical Properties

- NLGI Consistency Number = 2 to 6 (depending on stick or bulk form)
- Color: Light Brown
- Texture: Smooth
- Consistency: Smooth to Tacky (depending on stick or bulk form)
- High Chemical and Mechanical Stability
- Good Lubricity
- Water Insoluble
- High Temperature Additives
- Penetrants: Proprietary
- Temperature Range: -0° to 250° F
- Base Oils: Proprietary Synthetics

### Features

- H<sub>2</sub>O Resistant
- EP Additives
- Excellent Anti-Wear Properties
- Fully Additive Treated
- Contains Oxidation and Corrosion Inhibitors
- Contains NO Heavy Metals
- Non-toxic, Non-Hazardous - Environmentally Friendly

### Application Method

- Manual, Packing Injection Fitting, High Pressure Grease Gun or Automated Equipment (Air, Air/Hydraulic, Hydraulic, or Manual)

The information and the recommendations made in this data sheet are based upon collected data and believed by us to be correct. However, no guarantee or warranty of any kind, expressed or implied is made herein with respect to the merchandise described; and we assume no responsibility for the results or the use thereof.



Made in the USA

ESTD 1960

